

NOTES:

Item: SMOS10

Operating Speed: 0~300RPM, Higher speed can be custom

Working Temperature: -20°C ~ +80°C

Working Humidity: 10%~60%RH

Voltage Rating: 240VAC/DC

Current Rating: 2A

Dielectric Stength:500VAC@50Hz, 60s

Insulation Resistance:500MΩ@ 500VDC

Electrical Noise:1mΩMin

Contact Material :Precious metal

Lead wire: Teflon®UL 30AWG


Lead wire length:250mm

Material: All Stainless Steel Structure

Flange can be option

Drawings not actual size, dimensions are in millimeters

Model	NO. of Circuits	L
SMOS10-06	6	17.7
SMOS10-12	12	17.7

Drawn	JAM	TOLERANGCE EXCEPT AS NOTED		
Checked	TOM			
Checked	TOM			
ROVAL/DATE:		X.X ± .125 X.XX ± .015 X.XXX ± .005 ANGLES ± 0.5°	CUSTOMER:	
AINS INFORMATION WHICH IS PROPEIETARY TO CO.,LIMITED NO REPRODUCTION OR DOCUMENT OR TI IS CONTENTS , IN WHOLE OR VIHOUT THE WILTTEN CONSENT FROM COSMAU.			P/N:	
			REV: A.1	

THIRD ANGLE PROJECTION

